

RIVET AVEUGLE STANDARD



RIVET STANDARD TETE FRAISEE ALU/ACIER

Diamètre	Longueur	Plage de serrage
 4.8 mm	 2.5 mm	 650 N
2.4	6	2.0 – 4.0
	8	4.0 – 6.0

 6.0 mm	 3.1 mm	 850 N
3.0	6	1.5 – 3.5
	8	3.5 – 5.5
	10	5.5 – 7.0
	12	7.0 – 9.0
	16	9.0 – 13.0

 6.4 mm	 3.3 mm	 950 N
3.2	6	1.5 – 3.5
	8	3.5 – 5.5
	10	5.5 – 7.0
	12	7.0 – 9.0
	14	9.0 – 11.0
	16	11.0 – 13.0

Diamètre	Longueur	Plage de serrage
 8.0 mm	 4.1 mm	 1450 N
4.0	6	1.0 – 2.0
	8	2.0 – 4.0
	10	4.0 – 6.0
	12	6.0 – 8.0
	14	8.0 – 10.0
	16	10.0 – 12.0
	18	12.0 – 14.0
	20	14.0 – 16.0

 9.6 mm	 4.9 mm	 2250 N
4.8	8	1.5 – 3.5
	10	3.5 – 5.5
	12	5.5 – 7.5
	14	7.5 – 9.5
	16	9.5 – 11.5
	18	11.5 – 13.5
	20	13.5 – 15.5
	25	15.5 – 20.5
	30	20.5 – 25.5
	35	25.5 – 30.5

Existent aussi en version : acier/acier, inox/acier, inox/inox, alu/inox, alu/alu.
Nous consulter